

ROTAX® ENGINE	900 ACE Turbo R
Engine details	Liquid-cooled, four-stroke D.O.H.C., turbocharged
Cylinders	3
Displacement	899.0 cc
Bore	74 mm
Stroke	69.7 mm
Maximum engine speed	7900 RPM
Carburation	EFI
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	42 liters

Noble Bronze / Black			
3250 mm			
1280 mm			
1470 mm			
1097 mm			
600 mm			
3923 mm			
38 mm			

POWERTRAIN

2F/N/R with push-button reverse
pDrive
QRS
Hydraulic brake with braided steel brake line, plastic master cylinder

5	U	S	P	E	N	5	Г	U	Γ	V	

Front suspension	LFS+			
Front shock	KYB 36 Plus R			
Rear suspension	EasyRide with adjustment			
Center shock	KYB 46 Plus Kashima			
Rear shock	KYB 46 Plus Kashima			

DRY WEIGHT

Dry weight 313 kg

FEATURES

Frame	Radien-X
Skis	Blade DS+
Seating	Luxury Modular 1+1 with heating
Handlebar	U-type steel with hooks, low grab handle
Riser block height	Adjustable 125-165 mm
Starter	Electric
Reverse	Electromechanical
Heated throttle lever	Standard

Heated grips	Standard
Gauge	7.2-in. wide digital display
Mirrors	Standard
Windshield	Extra high with side deflectors
Hitch	Standard
Visor Plug front / rear	Front/Rear
USB power outlet	Front
Air radiator with fan	Yes
LinQ attachment	Multi-LinQ plate



^{*} Vehicle overall length without snowflap.