2023

SUMMIT EDGE



// WHAT'S NEW

- REV® Gen5 platform
- tMotion™ X rear suspension
- Premium LED headlights
- PowderMax† X-Light 3 in. with FlexEdge† available
- Narrower running boards and body work

// PACKAGE HIGHLIGHTS

• Rotax® 850 E-TEC® engine

ROTAX ENGINE

(Length x Width x Profile)

- High-quality HPG† shock package
- \bullet RASTM 3 front suspension with lightweight ski spindle and revised ski stopper \bullet Compact and lightweight deep-snow seat and revised ski stopper
- E-TEC SHOT[™] starter standard

850 F-TFC

PowderMax X-Light with FlexEdge:

154 x 16 x 3.0 in.

- \bullet Deep-snow running boards with large openings
- Pilot™ DS 3 skis
- Belt monitoring system

NOIAN ENGINE	OJO L-ILC
Engine details	Liquid-cooled, two-stoke, eRAVE™
Cylinders – Displacement	2 - 849 cc
Bore – Stroke (mm)	82 - 80.4
Carburation	E-TEC direct injection with additional booster injectors
Fuel type – Octane	Unleaded – 95
Fuel tank (L/US gal)	36/9.5
Oil tank capacity (L/qt)	3.4/3.6
POWERTRAIN Drive clutch Driven clutch	pDrive™ with clickers ORS Vent Plus
Drive sprocket pitch	89 mm/3.5 in.
DIMENSIONS	
Overall vehicle length	3,188 mm/125.5 in. (154 in.)
Overall vehicle width	1,080 to 1,110 mm/42.5 to 43.7 in.
Overall vehicle height	1,306 mm/51.4 in.
Ski stance	930 mm/36 in. adjustable

COLOR	
Catalyst Grey / Neo Yellow	
SUSPENSION	
Front suspension	RAS 3
Front shock	HPG
Front suspension travel	215 mm/8.5 in.
Rear suspension	tMotion
Center shock	HPG
Rear shock	HPG
Rear suspension travel	264 mm/10.4 in.
FEATURES Platform	REV Gen5
Skis	Pilot DS 3
Seating	Deep-snow compact and lightweight
Handlebar	Tapered U-shaped aluminum with J-hooks/Low grab handle
Riser block height	165 mm/6.5 in.
Starter	SHOT
Reverse	
Reverse	RER™
Brake system	RER™ Brembo†
Brake system	Brembo†
Brake system Heated throttle lever/grips	Brembo† Standard
Brake system Heated throttle lever/grips Gauge type	Brembo† Standard 4.5 in. digital





SUMMIT EDGE 165 850 E-TEC SHOWN