2023

EXPEDITION° SE



EXPEDITION SE 900 ACE TURBO R SHOWN

// PACKAGE HIGHLIGHTS

- Air Control Suspension (ACS) rear shock
- RAS $^{\text{TM}}$ X crossover front suspension
- 7.8 in. wide LCD display with BRP Connect available
- SC[†]-5U articulating rear suspension with locking mechanism (no tool required)
- 20 in. wide Multi-LinQ® plate with 56.7 kg cargo capacity
- Air radiator with fan
- Deep-snow running boards with large openings
- Removable passenger seat with heated grips
- Ultra-large LinQ utility cargo box with 135 L of storage
- Hitcl
- High-capacity battery
- Forward adjustable riser

- Easy-shift transmission (H-L-N) with electromechanical reverse (4-stroke)
- 23 in. ultra-high windshield with side deflectors
- Pivoting mirrors
- Pilot™ 7.4 skis
- Heated driver's visor power outlet
- pDrive™ clutch
- Backlit multifunction handlebar controls

ROTAX ENGINE	900 ACE TURBO R
Engine details	Liquid-cooled, four-stroke D.O.H.C., dry sump, turbocharged
Cylinders - Displacement	3 - 899 cc
Bore - Stroke (mm)	73 - 69.7
Carburation	EFI
Fuel type – Octane	Unleaded – 95
Fuel tank (L/US gal)	42/11.1
Oil tank capacity (L/qt)	3.3/3.5
POWERTRAIN	
Drive clutch Driven clutch	pDrive QRS Vent
Drive sprocket pitch	73 mm/2.86 in.
DIMENSIONS	SUSPENSION
Overall vehicle length 7 256 mm/13	20.2 in Erent euenopoien DAC V

DIFICHSIONS	
Overall vehicle length	3,256 mm/128.2 in.
Overall vehicle width	1,200 to 1,240 mm/47.7 to 48.8 in.
Overall vehicle height	1,515 mm/59.6 in.
Ski stance	1,000 mm/39 in. adjustable
Track	Silent Cobra WT:
(Length x Width x Profile)	154 x 20 x 1.5 in.
	Silent Ice Cobra WT:
	154 x 20 x 1.5 in. opt.

SUSPENSION	
Front suspension	RAS X
Front shock	HPG [†]
Front suspension travel	220 mm/8.7 in.
Rear suspension	SC-5U
Center shock	HPG
Rear shock	ACS (Air Control Suspension)
Rear suspension travel	239 mm/9.4 in.

COLOR

Catalyst Grey / Orange Crush

FEATURES

FEATURES	
Platform	REV® Gen4
Skis	Pilot 7.4
Seating	2-up modular with underseat storage
Handlebar	Standard with J-hooks/Grab handle
Riser block height	Adjustable- 120 mm/4.7 in.
Starter	Electric
Reverse	Electro-mechanic
Air radiator	High-efficiency w/ fan
Brake system	Brembo [†]
Heated throttle lever/grips	Standard (driver and passenger)
Gauge type	7.2 in. wide digital 7.8 in. wide LCD color (opt.)
Windshield	585 mm/23 in. with mirrors
Runner – Carbide	Square 3/8 in. – 4 in.
Bumpers (front/rear)	Heavy-duty/No



